

SIMPLEX CONTROL PANELS

Three Phase, 230 volt, for Sewage, Effluent & Non-Clog Pumps



Enclosure Type 4X Polycarbon

Circuit breaker For pump and control circuit

Motor starter IEC rated with class 10 overload

HOA switch Three position toggle HP rated

Alarm switch Three position toggle HP rated

Run light
Transformer
With fuse protection
Alternating relay
Moisture sensor*
Temp sensor*
With lead selector switch
Seal fail circuit and light
Heat sensor connections

Bracket Bright aluminum

Fuse Control and alarm sized at 3 amps

Terminal strip Box type lugs sectional

Wiring Color coded

Visible alarm 360 degree flashing

Audible alarm Piezo buzzer

Level control Requires 4 floats rated at 2 amps

Certifications UL 508A *Requires sensor to be in pump.

Consult factory for other available options. Some options may require an increase in the enclosure size.

Volts	Phase	Amps	Part number
230	3	2.4 - 4	BP23S4XNM004
230	3	4 - 6	BP23S4XNM006
230	3	6 - 10	BP23S4XNM010
230	3	9 - 12	BP23S4XNM012
230	3	10 - 16	BP23S4XNM016
230	3	16 - 18	BP23S4XNM018
230	3	18 - 24	BP23S4XNM024
230	3	24 - 32	BP23S4XNM032
230	3	32 - 40	BP23S4XNM040

NOTE: Overloads must be located in pump.





