Float & Splice Box Wiring Diagram





814 AIRWAY AVENUE

SUTHERLIN, OREGON

97479-9012


TELEPHONE:

(541) 459-4449

FACSIMILE:

(541) 459-2884

Float Arrangement



Float Types



Typical Orenco float model: B

Specs: contact - normally open differential - 3" min. power rating - signal

Possible substitutions: C,D

To Terminal To Terminal To Ground Terminal **Cord Grip** Hand tighten each cord grip so that the cord will not easily slide through the grommet. To Terminal To Terminal **High Level Alarm Pump Cord** Timer Override On & Off To Terminal Timer On & Off

Splice Box Wiring

Float Tag Colors

- Y Yellow
- R Red
- **P** Purple
- **O** Orange
- **R** Blue
- **F** Grev
- G Green
- W White

Note: Multi-function floats will have more than one marker

Attention: Failure to follow splicing instructions will void warranty

* Refer to drawing EIN-SB-SB-1 for splicing instructions.

Kev



Black Wire White Wire







Heat Shrink & Butt Connector *

Note: In systems which include floats, this drawing replaces drawing no. "EDW-FA-S-3"

Control Panel Series

Float Function Color Code

Splice Box Model

Drawing No.

S PT

(YG)R

SB₃

EDW-FS-S-6

EDW-FS-S-6 Rev 1.0 ©07/13/01