



by Schneider Electric

List Price \$32.40 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Action	Standard Action
Application	To control electrically driven water pumps
Actuator Type	Diaphragm
Differential Type	Adjustable
Approvals	UL Listed File: E12158 CCN NKPZ - CSA Certified File: LR25490
Contact Arrangement	DPST
Enclosure Rating	NEMA 1
Depth	2.78 Inches
Diaphragm	Nitrile (Buna N)
Differential	15 to 30 PSIG
Enclosure Type	General Purpose (Indoor)
Marketing Trade Name	Pumptrol
Flange Material	Zinc Plated Steel
Maximum Voltage Rating	575VAC
Horsepower Rating (3-Phase)	2HP@115VAC - 3HP@230VAC - 1HP@460/575VAC
Height	2.80 Inches
Horsepower Rating (1-Phase)	1.5HP@115VAC - 2HP@230VAC
Includes	Maintained manual cut-out lever
Maximum Allowable Pressure	220 PSIG
Mounting Type	Bracket
Weight	1.13 Pounds
Number of Poles	2-Pole
Pressure Connection	0.25 Inch NPSF
Pressure Setting	40 to 60 PSIG
Range on Decreasing Pressure	10 to 45 PSIG
Range on Increasing Pressure	20 to 65 PSIG
Terminal Type	Screw Clamp
Type	F
Width	3.76 Inches

Shipping and Ordering

Category	21534 - Pressure Switches, Commercial, Individual Pack, Type FSG, FYG, FSW, FYW & FRG
Discount Schedule	CP7I
GTIN	00785901320418
Package Quantity	1
Weight	0.91 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

Generated: 08/10/2012 12:38:01

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.